

### **GLENIUM 7700**

Version 1.2 04/23/2007

### 1. PRODUCT AND COMPANY INFORMATION

Company **BASF Construction Chemicals. LLC** 

> BASF Admixtures, Inc. 23700 Chagrin Blvd BEACHWOOD, OH 44122

Telephone 216-839-7500

BASF ER HOTLINE: 800-832-4357 Emergency telephone number

CHEMTREC: 800-424-9300

CHEMTREC (Outside Continental US): 703-527-3887

Product name **GLENIUM 7700** 

MSDS ID No. 11896

**TSCA Inventory** All components of this product are included, or are exempt from inclusion, in the EPA

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL This product contains material not included on the Canadian Domestic Substance List

(DSL).

**Product Use Description** Admixture

### 2. HAZARDOUS INGREDIENTS

Does not contain hazardous chemicals as defined by 29 CFR 1910.1200 and WHMIS.

### 3. HAZARDS IDENTIFICATION

**PHYSICAL** HMIS® Rating **FLAMMABILITY HEALTH HAZARD** 1

WHMIS Class D2B

Primary Routes of Entry Eye contact

Skin contact

**Effects of Overexposure** 

Inhalation Can cause slight irritation.

Skin Can cause slight irritation.

Eyes Can cause slight irritation.

Ingestion Can cause slight irritation.

No known information available. Chronic exposure



### **GLENIUM 7700**

Version 1.2 04/23/2007

## 4. FIRST AID MEASURES

Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek

medical attention.

Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation

persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a

person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an

unconscious person.

Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing

has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate

medical attention.

## 5. FIRE-FIGHTING MEASURES

Flash point : Not combustible.

Autoignition temperature : not applicable

Lower explosion limit : not applicable

Upper explosion limit : not applicable

Suitable extinguishing media : Use extinguishing agent suitable for type of surrounding fire.

Fire and Explosion Hazards : Containers can build up pressure if exposed to heat (fire). Cool closed containers

exposed to fire with water spray.

Special Fire-fighting Procedures : As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH

approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up : Wear appropriate protective equipment (refer to section 8). Take action to eliminate

source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse

residual stain with water.

#### 7. HANDLING AND STORAGE

Handling : Keep out of reach of children. For personal protection see section 8.

Storage : Keep tightly closed.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION



### **GLENIUM 7700**

Version 1.2 04/23/2007

Eye protection : Wear as appropriate:

safety glasses with side-shields

goggles face-shield

Hand protection : Wear as appropriate:

impervious gloves

Body Protection : Wear as appropriate:

impervious clothing preventive skin protection

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are

facing concentrations above the exposure limit they must use NIOSH approved

respirators.

Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in

confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety

practice.

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their

TLVs during the use of this product.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Color : purple-brown

Physical State : liquid

Odor : mild

pH : 5

Odor Threshold : No information available.

Vapor Pressure : No information available.

Vapor Density : No information available.

Boiling point/range : No information available.

Freeze Point : No information available.

Water solubility : dispersible

Specific Gravity : 1.064

Viscosity : Approx.235 cps

Evaporation rate : No information available.

Partition coefficient (n-

octanol/water)

No information available.



### **GLENIUM 7700**

Version 1.2 04/23/2007

VOC Concentration as applied

(less water and exempt

solvents)

10. STABILITY AND REACTIVITY

Stability : Stable under recommended storage conditions.

Conditions to avoid : Prolonged exposure to high temperatures

: 0 g/l

Hazardous polymerization : Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

Product Type Value Species Exposure time
LC50 no data available

**Acute oral toxicity** 

<u>Type</u> <u>Value</u> <u>Species</u>

Product LD50 (Oral) no data available

Acute dermal toxicity

<u>Type</u> <u>Value</u> <u>Species</u>

<u>Product</u> LD50 (Dermal) no data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT : Proper shipping name Not regulated



### **GLENIUM 7700**

Version 1.2 04/23/2007

### 15. REGULATORY INFORMATION

#### **SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

not applicable

### **SARA 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

#### **CERCLA**

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

RQ CAS No. Chemical Name

No CERCLA chemicals exist in this product above reportable concentrations.

#### TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

CAS No. Chemical Name

There are no TSCA 12(b) Chemicals in this product.

### California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

CAS No. Chemical Name
75-21-8 ETHYLENE OXIDE

123-91-1 DIOXANE

### 16. OTHER INFORMATION

Legend : N.E. - Not Established

TLV - Threshold Limit Value STEL - Short Term Exposure Limit PEL - Permissible Exposure Limit

CEIL - Ceiling

Prepared By : Environment, Health and Safety Department



### **GLENIUM 7700**

Version 1.2 04/23/2007

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.