

MB-AE[™] 90

Version 1.2

06/27/2006

1. PRODUCT AND COMPANY INFORMATION

Company	:	BASF Corporation 23700 Chagrin Blvd BEACHWOOD, OH 44122
Telephone	:	216-839-7500
Emergency telephone number	:	(800) 424-9300 (703) 527-3887 (Outside Continental US)
Product name	:	MB-AE™ 90
MSDS ID No.	:	10059
TSCA Inventory	:	All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canadian DSL	:	All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

2. HAZARDOUS INGREDIENTS

Does not contain hazardous chemicals as defined by 29 CFR 1910.1200 and WHMIS.

3. HAZARDS IDENTIFICATION

HMIS [®] Rating		HEALTH 1	FLAMMABILITY 0	PHYSICAL HAZARD 0			
WHMIS Class	:	D2B					
Primary Routes of Entry	:	Inhalation Eye contact Skin contact					
Effects of Overexposure							
Inhalation	:	Can cause slig	ght irritation.				
Skin	:	Can cause slight irritation.					
Eyes	:	Can cause slight irritation.					
Ingestion	:	Can cause slig	ght irritation.				
Chronic exposure	:	No known info	rmation available.				



MB-AE[™] 90

Version 1.2

06/27/2006

4. FIRST AID MEASURES		
Eye contact	Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.	
Skin contact	Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.	
Ingestion	Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a pers vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.	
Inhalation	Remove victim from exposure. If difficulty with breathing, administer oxygen. If breath has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immedia medical attention.	

5. FIRE-FIGHTING MEASURES

Flash point	:	not applicable
Autoignition temperature	:	not applicable
Lower explosion limit	:	not applicable
Upper explosion limit	:	not applicable
Suitable extinguishing media	:	Use extinguishing agent suitable for type of surrounding fire.
Fire and Explosion Hazards	:	Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.
Special Fire-fighting Procedures	:	As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

```
Methods for cleaning up : Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.
```

7. HANDLING AND STORAGE

Handling	:	Keep out of reach of children. For personal protection see section 8.
Storage	:	Keep tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Material Safety Data Sheet



MB-AE™ 90		
Version 1.2	06/27/200)6
Eye protection	: Wear as appropriate: safety glasses with side-shields goggles face-shield	
Hand protection	: Wear as appropriate: impervious gloves	
Body Protection	: Wear as appropriate: impervious clothing preventive skin protection	
Respiratory protection	 In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators. 	
Hygienic Practices	: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.	
Engineering Controls	: Local exhaust ventilation can be necessary to control any air contaminants to within thei TLVs during the use of this product.	r

9. PHYSICAL AND CHEMICAL PROPERTIES

Color	:	dark brown
Physical State	:	liquid
Odor	:	none
рН	:	10.3 - 11.5
Odor Threshold	:	no data available
Vapor Pressure	:	no data available
Vapor Density	:	Heavier than air
Boiling point/range	:	212 °F (100 °C)
Freeze Point	:	32 °F (0 °C)
Water solubility	:	completely soluble
Specific Gravity	:	1.012 - 1.020
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n- octanol/water)	:	no data available
VOC Concentration as applied	:	0 g/l

Material Safety Data Sheet

MB-AE[™] 90

Version 1.2

(less water and exempt solvents)

10. STABILITY AND REACTIVITY

Stability	:	Stable under recommended storage conditions.			
Conditions to avoid	:	Prolonged exposure to high temperatures			
Materials to avoid	:	strong acids metals			
Hazardous decomposition products	:	Hydrogen in contact with aluminum or zinc. Oxides of carbon nitrogen oxides (NOx)			
Hazardous polymerization	:	Will not occur under normal conditions.			

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity Product	<u>Type</u> LC50	<u>Value</u> no data available	<u>Species</u>	Exposure time
Acute oral toxicity Product	<u>Type</u> LD50 (Oral)	<u>Value</u> no data available	<u>Species</u>	
Acute dermal toxicity Product	<u>Type</u> LD50 (Dermal)	<u>Value</u> no data available	<u>Species</u>	

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.



06/27/2006

The Chemical Company

MB-AE™ 90

Version 1.2

06/27/2006

14. TRANSPORT INFORMATION

DOT: Proper shipping nameNot regulatedIATA: Proper shipping nameNot regulated

15. REGULATORY INFORMATION

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD

<u>SARA 313</u>

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

RQ CAS No. Chemical Name

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

CAS No. Chemical Name

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

CAS No. Chemical Name

16. OTHER INFORMATION

Legend

N.E. - Not Established TLV - Threshold Limit Value STEL - Short Term Exposure Limit

Page 5 of 6



MB-AE[™] 90

Version 1.2

06/27/2006

PEL - Permissible Exposure Limit CEIL - Ceiling

Prepared By

: Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.