Page 1

Date of preparation: 07/01/04 1003360

SECTION I

Manufacturer : W. R. MEADOWS, INC. - H M I S -

Address : 300 Industrial Drive | Health : 0 | : Hampshire, Illinois 60140 | Flammability : 0 |

|Reactivity : 0 | |Personal Protection : |

Telephone # : (847) 683-4500

Emergency # : 1-800-424-9300 Chemtrec

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : DIVISION 3 Mfg. code I.D. : 1003360

Trade Name : ASPHALT EXPANSION JOINT FILLER

SECTION II-A HAZARDOUS COMPONENTS

			% by	SARA	VAPOR PRESSURE	LEL
No.	Component	CAS#	Weight	313	(mm Hg @ 20 C)	(@ 25 C)
1.	Petroleum Asphalt	8052-42-4	60-65	NO	N/A	N/A
2.	Limestone	1317-65-3	10-15	NO	N/A	N/A

None of the components of this product are recognized as carcinogenic. N/A: Not Applicable

ASPHALT EXPANSION JOINT FILLER is defined by OSHA (29 CFR Part 1910) as an "Article". A manufactured item which is formed to a specific shape or design during manufacture which does not release or otherwise result in exposure to a hazardous chemical under normal conditions of use.

SECTION II-B OCCUPATIONAL EXPOSURE LIMITS

		OSHA				ACGIH		
No.	PEL/TWA	PEL/CEILING	PEL/STEL	SKIN	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	5 mg/m ³ *	N/E	N/E	N/E	5 mg/m ³ *	N/E	N/E	N/E
2.	15mg/m ³ **	N/E	N/E	N/E	10 mg/m ^{3**}	N/E	N/E	N/E
N/E	= Not established	d *=	Asphalt fume	s	** = Total dust			

SECTION III PHYSICAL DATA

Boiling Point	: Not applicable	% Volatile by volume	: Not applicable
Evaporation Rate	: Not applicable	% Volatile by weight	: Not applicable
Vapor Density	: Not applicable	Weight per gallon	: Not applicable
nH I evel	· Not applicable	Annearance	· Solid asphalt hoard

SECTION IV HEALTH INFORMATION

EYE CONTACT: May cause mechanical irritation. **SKIN CONTACT:** May cause mechanical irritation.

INHALATION: Under normal use this product is not hazardous via inhalation.

INGESTION: This product has a low order of toxicity. If symptoms of gastrointestinal irritation develop, seek medical attention.

SIGNS AND SYMPTOMS: None with normal product use.

AGGRAVATED MEDICAL CONDITIONS: None known with normal product use.

OTHER HEALTH EFFECTS: From skin painting studies in laboratory animals, it has been concluded that some asphalts may possess weak carcinogenic activity. This means that workers who practice poor personal hygiene, and who are repeatedly exposed by direct skin contact with petroleum asphalt over many years, may potentially be at risk of developing skin cancer. Intermittent or occasional skin contact with petroleum asphalt is not expected to have serious health effects as long as personal hygiene measures, such as outlined in this material safety data sheet, are followed. In addition, asphalt vapors may contain polycyclic hydrocarbons, some of which are known to be carcinogenic. Therefore, prolonged breathing of vapors should be avoided.

SECTION V EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water to remove particulates.

SKIN CONTACT: Flush with water to remove particulates. Wash affected area with soap and water if available.

INHALATION: None normally required. **INGESTION:** None normally required.

Date of preparation: 07/01/04

Page 2 1003360

Date of preparation: 07/01/04

SECTION VI FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION

NFPA : NoneDOT : Not regulated

FLASH POINT: Greater than 400 degrees F

EXTINGUISHING MEDIA: Use water fog, chemical foam, or Carbon Dioxide. **SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:** None recognized.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None recognized.

SECTION VII REACTIVITY

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIALS TO AVOID: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products.

SECTION VIII EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: None required with normal product use. **PROTECTIVE CLOTHING:** None required with normal product use.

ADDITIONAL PROTECTIVE MEASURES: Not applicable.

SECTION IX ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES: Not applicable: product is a solid.

WASTE DISPOSAL: Permitted landfill. Consult Federal, State, and local regulations for compliance.

SECTION X ADDITIONAL PRECAUTIONS

Store in a cool dry place away from direct sources of heat.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

Date of preparation: 07/01/04